BMW Motorrad Maintenance schedule K 75 / K 75 S/C/RT / K 1 / K 100 / K 100 RT/LT up to 1993 onlys K 100 RS (2V)/(4V) up to 1993 onlys



			n miles	iles	u /	uo
Customer	Licence No.	Mileage	BMW Inspection at 1000 km/600 mile	BMW Maintenance Service every 7500 km/4,500 miles	BMW Inspection every 15000 km/ 9,000 miles	BMW Annual Inspection
Job Order No.	Date	Mechanic's signature	BMW In at 1000	BMW M Service 7500 km	BMW In every 14 9,000 m	BMW Annual
Change oil when engine at	regular operating tempera	ature, renew oil filter element				
Change oil in gearbox, final drive and telescopic fork Clean inductive sensor at rear wheel at least once a year						
Grease upper/lower clutch cable nipples and side/centre stand pivots						
Renew intake air cleaner element						
Renew fuel filter element every 40,000 km (24,000 miles)						
Check hose clips on fuel and cooling system for leaks and take up slack if necessary Check coolant level and concentration						
Renew coolant after at least every 2 years *)						
Check brake system connections and lines for leaks, damage and incorrect positioning Check brake fluid level at front and rear						
Renew brake fluid at least once a year *)						
Check brake pads and discs for wear only motorcycles with ABS every 7500 km / 4,500 miles						
Check brake calipers for correct operation/freedom from leaks						
[ABS] Check sensor gap for ABS at front and rear						
[ABS] Check sensor/pulse wheel for ABS at front and rear for contamination						
Check operation of electric side stand switch (angle)						
Check clutch operating clearance						
Check free travel at throttle and cold-start (choke) cables						
Renew spark plugs						
[MOTRONIC] Read out fault memory						
Check valve clearences [1000 km / 600 miles K 75 models only] adjust if necessary*)						
Renew the lining on the chain tensioner rail every 60,000 km (36,000 miles)						
Check steering head bearing play						
Check battery acid level at least every 3 months						
Clean and grease the battery posts *)						
Take up slack at bolts and nuts: - power unit to frame - suspension strut mounts - side/center stand pivot - rear wheel studs						
Apply silicone spray to guide rods of adjustable windshield (only K 100 LT, K 75 RT)						
Final inspection with safety/operating check: - condition of tyres and wheels, tyre pressures - lights and signal systems, telltale and warning lights - clutch and gear shift - handbrake and footbrake, ABS - steering, instruments - idle speed and CO content of exhaust						
Recommendation: In severe operating condition	s, grease the throttle twistg	rip and steering head bearings at least ever	v 30.000 km	(18.000 m	iles) *)	